

**NAME**

bibmradd.pl – add MR numbers to papers in a given bib file

**SYNOPSIS**

bibmradd [-d] [-f] [-e 1|0] [-o *output*] *bib\_file*

**OPTIONS**

- d** Debug mode
- e** If 1 (default), add an empty mrnumber if a mr cannot be found. This prevents repeated searches for the same entries if you add new entries to the file. Calling **-e 0** suppresses this behavior.
- f** Force searching for MR numbers even if the entry already has one.
- o *output***  
Output file. If this option is not used, the name for the output file is formed by adding `_mr` to the input file

**DESCRIPTION**

The script reads a BibTeX file. It checks whether the entries have mrnumbers. If not, it tries to find the numbers from Internet sites. The result is a BibTeX file with `mrnumber=...` fields added.

The name of the output file is either set by the **-o** option or is derived by adding the suffix `_mr` to the output file.

See the `bibdoiadd` script for more details on the processing.

**AUTHOR**

Boris Veytsman

**COPYRIGHT AND LICENSE**

Copyright (C) 2014–2026 Boris Veytsman

This is free software. You may redistribute copies of it under the terms of the GNU General Public License <<http://www.gnu.org/licenses/gpl.html>>. There is NO WARRANTY, to the extent permitted by law.